

VLT® Micro Drive FC 51

(044) 522-80-19

Универсальный компактный привод на мощность до 7,5 кВт

0-100%, 0-200 (VVC+), 0-400 (U/f)



- 1 -
- 2 -
- 3 -
- 4 -
- 5 -

- 200-240 , 1
- 50/60
- IP20/IP21()
- w/RFI Class A1/B
- ()

					*
1	0,18	1,2		132F0001	137,98
	0,37	2,2		132F0002	148,60
	0,75	4,2		132F0003	171,15
2	1,5	6,8		132F0005	230,86
3	2,2	9,6		132F0007	287,91

- 380-480 , 3
- 50/60
- IP20/IP21()
- w/RFI Class A1/B
- ()

					*
1	0,37	1,2		132F0017	199,33
	0,75	2,2		132F0018	227,28
2	1,5	3,7		132F0020	296,96
	2,2	5,3		132F0022	370,62
3	3	7,2		132F0024	426,30
	4	9		132F0026	460,64
	5,5	12		132F0028	553,01
	7,5	15,5		132F0030	627,15
4	11	23		132F0058	908,53
	15	31		132F0059	1049,04
5	18	37		132F0060	1296,71
	22	43		132F0061	1522,96

- / - 5(1)
- (0-10 , 0/4-20) - 2
- (0/4-20) - 1
- () - 1
- .c - RS485

LCP11	132B0100	25,94
LCP12	132B0101	25,94
LCP	132B0102	11,97
(LCP11 - IP54, LCP12 - IP21)		
IP21 1	132B0108	11,97
IP21 2	132B0109	14,63
IP21 3	132B0110	17,29
DIN- (1)	132B0111	3,72

